A. Introduction:

FTP-WatchDog is a reliable application program that can be used to send files using the File Transfer Protocol. FTP-WatchDog typically is used with software applications that periodically produce an image, data or text file. FTP-WatchDog detects the new file and automatically sends it to an FTP server on a website.

The FTP-WatchDog user interface is in German, so if you are unable to read it, the translations and instructions below will help you. These instructions apply only to FTP-WatchDog version 3, which is slightly different than version 2. Not all variations in FTP-WatchDog setup are covered here.

B. Installation:

- 1. Download the free installation program ftp-watchdog-setup.exe from: http://toolsandmore.de/Central/Produkte/Software/Internet/Webmaster/FTP-Watchdog/.
- 2. Installation is straight-forward but step-by-step screenshots and translations are provided in Appendix II. Upon completion, the application Settings file will open. Refer to the screenshot below and the next section. The original program has German language text, and the screenshot shows English translations.

Image: Trevaluation of the spectrum of the spec	Op New Setti Settings	en ngs Save Settings	Open D Log I File I	elete Log File	Go To l Help	Jser Direc About	ctory Exit	progra	m le
FTP Server Name Name des FTP-Servers: Passives FTP. FTP Username FTP-Benutzername: FTP-Password FTP Password FTP-Passwort. Image: Construction of the second of the	Neu Öffn	7 Speichern	Protokoll k	🥑 😥 öschen Verz. öffner	n Hilfe	i) Info E	Beenden Au	Benden	sive FTP
FTP Username FTP-Benutzername: FTP Password FTP-Passwort Local Directory Lokales Verzeichnis: FTP Directory FTP-Verzeichnis: Only 1 Level Nur 1 Ebene tief sucher: File Types Zu übert: Dateityper: All Only These File Types Zu übert: Dateityper: Ignore Patterns Zu ignorierende Muster: Dateinamen wandeln: Nein: Bebehalten Nor Retain Upload-Intervalt sofort Play Sounds Sounds abspieler: Upload 1 x alles hochlader: Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Norpal.png 0K [18:41:50] Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Norpal.png 0K [18:41:50] Lipload interval Confirm Deleting Files from FTP Server	FTP Serv	er Name -	Name des FTP-	Servers:					Passives FTP:
FTP Password FTP-Passwort Local Directory Lokales Verzeichnis: FTP Directory FTP-Verzeichnis: Only 1 Level Nur 1 Ebene tief sucher: Value Nur 1 Ebene tief sucher: Value Nur 1 Ebene tief sucher: Ignore Patterns Zu übert: Dateinamen wandeln: Nei:: Beibehalten Nor: Reibehalten Nor: Reibehalten Nor: Sounds abspieler: Upload-Intervall: sofot 1X Upload 1 x alles hochlader: Löschen von Dateien auf FTP-Server bestätigen: Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Norpal.png 0K [18:41:50] Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Norpal.png 0K [18:41:50] Upload interval Confirm Deleting Files from FTP Server	FTP Us	ername —	FTP-Benutz	zername:					
Local Directory Lokales Verzeichnis: FTP Directory FTP-Verzeichnis: Only 1 Level Nur 1 Ebene tief suchen: Nur 1 Ebene tief suchen: All Only 1 Level Nur 1 Ebene tief suchen: File Types Zu übertr. Dateitypen: Ignore Patterns Zu ügnorierende Muster: Ignore Errors Fehler ignorieren: Play Sounds Sounds abspielen: Upload-Intervali sofott 1X Upload 1 x alles hochlader: Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K (18:41:50) Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K (18:41:50)	FTP Pa	ssword –	FTP-P	asswort:					
FTP Directory FTP-Verzeichnis: Only 1 Level Nur 1 Ebene tief sucher: File Types Zu übert: Dateityper: Ignore Patterns Zu ignorierende Muster: Ignore Errors Fehler ignorierende Muster: Play Sounds Sounds abspieler: Upload-Intervali: sofort 1X Upload 1 x alles hochlader: Uzischen von ftp://reeve.com/kwww.reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K [18:41:50] Löschen von ftp://reeve.com/kwww.reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K [18:41:50]	Local D	irectory –	Lokales Ver	zeichnis:					
Only 1 Level Nur 1 Ebene tief suchen: All Only These File Types Zu übertr. Dateitypen: All © Nur diese: Ignore Patterns Ignore Patterns Zu ignorierende Muster: Convert Filenames Ignore Errors Fehler ignorierende Muster: Dateinamen wandeln: Nein: Beibehalten — No: Retain Play Sounds Sounds abspieler: Upload-Intervali: sofort Immediately 1X Upload 1 x alles hochlader: Löschen von Dateien auf FTP-Server bestäliger: File Autostart dieser FTP-Verbindung aktivierer: File Autostart Löschen von ftp://reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K [18:41:50] Enable Autostart Upload interval Confirm Deleting Files from FTP Server	FTP Di	rectory -	FTP-Ver	zeichnis:					
File Types Zu übertr. Dateityper: Alle I IV rises: Ignore Patterns Zu ignorierende Muster: Convert Filenames Ignore Errors Fehler ignorieren: IV Play Sounds Sounds abspieler: Upload-Interval: Sofot 1X Upload 1 x alles hochlader: Löschen von Dateien auf FTP-Server bestätiger: IV Löschen von ftp://reeve.com/www.reeve.com/Applications/PlanePlotter/NA002_W7_Nornal.png 0K [18:41:50] Enable Autostart Upload interval Confirm Deleting Files from FTP Server	Only 1	Level -	Nur 1 Ebene tief	suchen: 🔽 👝 🖊		ly These			
Ignore Patterns Zu ügnorierende Muster: Convert Filenames Ignore Errors Fehler ignorieren: Dateinamen wandeln: Nein: Beibehalten — No: Retain: Play Sounds Sounds abspielen: Upload-Interval: sofort — Immediately 1X Upload 1 x alles hochladen: Löschen von Dateien auf FTP-Server bestätigen: Löschen von ftp://reeve.com/www.reeve.com/Applications/PlanePlotter/NA002_W7_Nornal png 0K [18:41:50] Enable Autostart Upload interval Confirm Deleting Files from FTP Server	Filo T	Vnoc	Zujibati Da		Mur diana:				
Ignore Patterns 24 gnoneerde Muster. COnvert Friendrites		ypes —		Muster	Nui diese.	Convert F	ilonomoo		
Ignore Errors Fehler ignorierer: Dateinamen wandeh: Nein: Beibehalten - No: Retain? Play Sounds Sounds abspieler: Upload-Intervall: sofort - Immediately 1X Upload 1 x alles hochlader: Löschen von Dateien auf FTP-Server bestätiger: Image: Comparison of the state of the	Ignore P	-allerns -	2 Zu ignolielende	muster. J			lienames		
Play Sounds Sounds abspieler: Upload-Intervali: sofort Immediately 1X Upload 1 x alles hochlader: Immediately Immediately Immediately 1X Upload 1 x alles hochlader: Immediately Immediately Immediately Enable Watchdog Watchdog aktiv: Immediately Immediately Immediately Löschen von ftp://reeve.com/www.reeve.com/Applications/PlanePlotter/NA002_W7_Normal.png 0K [18:41:50] Enable Autostart Upload interval Confirm Deleting Files from FTP Server	Ignore	Errors -	Fehler igr	norieren: 🔽 🛛 D	ateinamen wan	leln: Nein: Beibeh	alten — No:	Retain	
1X Upload 1 x alles hochlader: Image: Construction of the state of the sta	Play S	ounds —	Sounds at	bspielen:	Upload-Inter	vall: sofort —	Immediate	ly 🖃	
Enable Watchdog Watchdog aktiv: 🔽 Autostart dieser FTP-Verbindung aktivieren: 🔽 Enable Autostart Enable Autostart Upload interval Confirm Deleting Files from FTP Server	1X U	oload —	1 x alles ho	chladen:	Lösch	en von Dateien au	f FTP-Server bes	tätigen:	
Löschen von ftp://reeve.com/www.reeve.com/Applications/PlanePlotter/NA002_W7_Normal.png 0K [18:41:50] Enable Autostart Upload interval - Confirm Deleting Files from FTP Server	Enable W	vatchdog —	Watchde	og aktiv: 🔽	1	Autostart dieser FT	P-Verbindung akt	ivieren: 🔽	
Upload interval – Confirm Deleting Files from FTP Server	Löschen von ftr:///ww		com/Applications/	PlanePlotter/NA002 \u	7 Normal res C	K [18:41:50]		L Enab	le Autostart
Upioad interval — Confirm Deleting Files from FTP Server	Losener for the	570.00m - MMY.10670.	com/~ppileduolis/1		roundeprig c		ation of Films	for an ETE	
				upload interv		Johirm Del	eung Files	IIOM FIF	Server

C. Setup and Use FTP-WatchDog V3:

- 1. The following describes each field and the action to be taken.
 - a. Refer to the screenshot, and fill in or check the following fields (additional screenshots of actual setups are provided in Appendix I):
 - <u>FTP Server Name</u> (use the domain name and extension, as in *myserver.com*)
 - <u>FTP Username</u> (must match the username allowed access to your FTP site)
 - <u>FTP Password</u> (must match the password allowed access to your FTP site)
 - **Passive FTP** (if the PC running FTP-Watchdog is behind a router with Network Address Translation (NAT) enabled, checking this box will make file transfers much more reliable)
 - b. Now fill in the following fields:
 - <u>Local Directory</u> (full path where the files are located on your PC, example *c:\myfiles\datafiles*. Enter only the path, no filename; see par. c. Alternately, browse to the folder by clicking the Folder icon on the far right of the field)
 - <u>FTP Directory</u> (full path on the remote site where the file is to be sent, typically a folder on your website, example */mydata/imagefiles*). Enter only the path, no filename; see par. c. <u>Note</u>: The <u>FTP</u> <u>Directory</u> must be setup before using FTP-WatchDog; FTP-WatchDog does not establish its own directories
 - c. Select file types to be sent
 - <u>File Types</u>, consisting of two radio buttons and a field

Select the radio button **All** to send any file in the Local Directory (par. b) regardless of filename or extension. Do not enter any file types or extensions in the adjacent field.

Select the radio button **Only These** to send the file types or filenames listed in the adjacent field. Enter all filenames and extensions in the adjacent field.

Do not put any path information in the field (the path is specified in the <u>FTP Directory</u> field, see par. b). Be sure there are no other files in the <u>Local Directory</u> except the files to be sent. You can list more than one file or extension – separate them with a space.

<u>e-CALLISTO</u>: To send time-stamped Callisto FITS data files specify only the extension with leading dot (or period), as in .fit. If FITS files are to be sent to more than one server or website, a separate setup file is needed for each location (see par. 2 for running multiple instances of FTP-WatchDog). See Appendix I for specific examples.

<u>SAM</u>: To send only SAM magnetogram image files specify the filename sam_data.png. To send any PNG-type image file specify only the extension .png (be sure to include the leading dot or period). See Appendix I for specific examples.

- d. Leave the following field blank:
 - <u>Ignore Patterns</u> (Use this field to specify directories or files in the <u>Local Directory</u> that you do not want sent to the FTP server. This is useful if you have a temporary folder or backup directory that you do not want sent to the FTP server, for example \temp or \backup. FTP-WatchDog will ignore these entries and not upload them. Separate multiple entries by spaces)
- e. Setup the following boxes and fields:
 - Ignore Errors (check)
 - **Play Sounds** unchecked (unless you want to be driven crazy, but this can be useful when troubleshooting FTP problems)

- □ 1X Upload (normally unchecked. Check this box to resend files in the Local Directory after an FTP server, PC or internet failure that prevented some of the files from being uploaded. FTP-WatchDog will upload all files and then automatically gray out the box when all files have been successfully uploaded. If a subsequent upload failure occurs, the unchecked box □ will become available so that this function may be used again)
- Enable WatchDog (check to allow FTP-WatchDog to send files; \Box uncheck if you want it to stop)
- Change or Convert Filename: From drop-down menu, select No: Retain (*Nein: Beibehalten*)
- Upload Interval: <u>10 seconds</u> (10 *Sekunden*) for most applications. (This drop-down menu can be used to set the upload interval over a very wide range of time intervals from immediately (*sofort*) to seconds (*Sekunden*), minutes (*Minuten*), hours (*Stunden*) or days (*Tage*). The longer intervals could be useful where internet access is by dialup modem. The Immediately (*sofort*) setting is not recommended because of the CPU resources required to rapidly scan for appearance of new files)
- Confirm Deleting Files from FTP Server (normally uncheck. If you delete or rename a file in the Local Directory, FTP-WatchDog will delete them on the FTP server. If this box is checked, FTP-WatchDog will ask for confirmation before deleting the files from the server)
- Enable Autostart (check to cause FTP-WatchDog to automatically open and start sending when you reboot the PC; \Box uncheck if you do not want the program to automatically open and start sending on reboot)
- f. After you have everything setup properly, click the Save icon on the Toolbar. The default filename is <u>Unnamed FTP-Setting.ftpwd</u> (in German). If desired, change to another name, such as <u>My_Application_Setup</u> (extension will be appended automatically). At this time FTP-WatchDog should start sending files. The howling dog icon in the taskbar system tray should turn green to indicate that FTP-WatchDog is active.



- 2. You can setup different configurations and **Save** as many of them as you need. For most applications, one Settings file is sufficient; however, if you want to send files to more than one website or FTP server, you can run multiple instances of FTP-WatchDog. In this case, you would have a separate Settings configuration file for each one. Care is required when running multiple instances to avoid overloading CPU resources (do not use the <u>Immediate</u> upload interval).
- 3. When FTP-WatchDog starts, it automatically loads the last used Settings file. You can manually load a Settings file by clicking the **Open** icon or setup a new file by clicking the **New** icon on the Toolbar. If setting up multiple instances, be sure to watch CPU usage. CPU usage depends on the **Upload Interval** with <u>Immediate</u> upload interval using the most CPU resources, but PC characteristics also will have an effect.
- 4. If you have problems getting file transfers to work properly, click the **Open Log File** icon on the Toolbar. This opens a text file of all activity. Although the logs are in German, it should be apparent what is causing the problem (FTP server error responses may be in English anyway). Alternately, you can use http://translate.google.com/ to translate the logs. Copy the log entry in question and Paste it into the Google

text entry box. Be sure to select German > English translation in the dropdown boxes. If you want to start fresh logs, click the **Delete Log File** icon.

<u>Note</u>: FTP-WatchDog log files grow as the program runs and should be regularly deleted so they do not get larger than 45 KB. Notepad cannot open a file that exceeds 54 KB and does not allow editing if the file size reaches between 45 and 54 KB.

- 5. To hide the user interface, click the **Hide** icon on the Toolbar. This will hide the interface window but the program will continue to run in the background and it will be available from the taskbar. If you see a howling dog icon in the taskbar, FTP-WatchDog is running. If the icon is red, FTP-WatchDog is disabled and not sending; if the icon is green, it is enabled and sending.
- 6. To shutdown and exit FTP-WatchDog, click the **Exit** icon on the taskbar. This will terminate the FTP session and shutdown the program. However, if **Autostart Enabled** is checked, FTP-WatchDog will automatically open when the PC is rebooted.
- 7. To restart the program, from the main Windows screen go to Start All Programs Tools&More FTP-Watchdog FTP-WatchDog. FTP-WatchDog automatically loads the last saved Settings file. If Enable WatchDog was checked in setup, the program will start sending immediately and the taskbar icon should be green. If Enable WatchDog was not checked, the icon will be red. Click the taskbar icon and the user interface window will appear. Check the Enable WatchDog box and click Save. The taskbar icon should turn green, indicating that the program is sending.
- 8. If desired, you can put a Shortcut on your Desktop by right-dragging the FTP-WatchDog.exe file from the folder C:\Program Files\Tools&More\FTP-Watchdog to the Desktop and selecting Create Shortcuts here.
- 9. Test the **Autostart Enabled** feature by rebooting the PC. When the PC reboots, FTP-WatchDog should automatically open and start and you should see the howling dog icon in the taskbar. The icon should be green if **Enable WatchDog** is checked in the Settings file.
- 10. When FTP-WatchDog sends a file, the howling dog icon momentarily turns from green to white and then back to green.
- 11. To uninstall the program, from the main Windows screen go to Start All Programs Tools&More FTP-Watchdog *Deinstallieren*.

Appendix I – Specific Application Setups

e-CALLISTO FITS File sent to ETH-Zurich server. Note: Send only FITS files to ETH (below).

FIP-wat	chdog - [Ca	llisto_FITS]								
Neu	Öffnen	Speichern	Protokoll	7 löschen	0 Verz. öffnen	2 Hilfe	1 Info	Beenden	Ausblenden	k
			Name des F	TP-Servers:	tpexchange.i	mvs.technik.fhn	w.ch			Passives FTP:
			FTP-Ber	nutzername:	solarradio					
			FTI	P-Passwort:	******					
	0		Lokales	/erzeichnis:	C:\CALLISTO	117\Data\				
9	21		FTPA	/erzeichnis:						
1			Nur 1 Ebene	tief suchen:						
			Zu übertr.	Dateitypen:	O Alle 💿	Nurdiese:	9			
	Con C		Zu ignorierer	nde Muster:		57				
	16		Fehle	r ignorieren:		ateinamen wand	leln: Nein: Be	ibehalten		
	N.									
d	A	1	Sound	s abspielen:		Upload-Inter	vall: 10 Seku	nden		
201		1 a	Sound:	s abspielen: hochladen:		Upload-Inter Lösch	vall: 10 Seku en von Dateie	nden n auf FTP-Serv	er bestätigen:	

e-CALLISTO Lightcurve Image File. Note: Lightcurves usually are sent to a user website (below).

Neu	Öffnen	Speichern	Protokoll	löschen Ver	D z. öffnen	? Hilfe	i) Info	Beenden	Ausblenden	
			Name des FTF	P-Servers: reev	e.com					Passives FTF
			FTP-Benu	itzername: reev	ecom					
			FTP-	Passwort: ****	***					
<u>.</u>	01		Lokales Ve	erzeichnis: C:\0	ALLIST0117	LCPlotter\Plot:	81			
9			FTP-Ve	erzeichnis: 7ww	w.reeve.com/	e-CALLISTO				
1			Nur 1 Ebene tie	ef suchen: 🔽	[
			Zu übertr. D	ateitypen: C	Alle 💽 Nur (diese: .png				
	Ser.		Zu ignorierend	de Muster:		-				
	e		Fehler i	ignorieren: 🔽	Datein	amen wandeln:	Nein: Beibeł	nalten		
<u>, 1</u>	10	N.	Sounds -	abspielen: 🔽	U	Ipload-Intervall:	10 Sekunde	n		• - *
	P.L	36	1 x alles h	iochladen: 🖵		Löschen v	on Dateien au	uf FTP-Serve	er bestätigen:	
in.					· · · · · ·		CREEK LINE OF T	DV-shinds	10.1	-

SAM Magnetogram Image sent at 1 minute intervals (below)

📕 FTP-Watchdog - [SAM_Magnetog	gram_Full_1min]	X
Neu Öffnen Speichern	Protokoll löschen	Verz. öffnen Hilfe Info Beenden Ausblenden
	Name des ETP-Servers:	reeve.com
	FTP-Benutzername:	reevecom
	FTP-Passwort:	MANANANAN
	Lokales Verzeichnis:	C:\Program Files\SAM\Data\
	FTP-Verzeichnis:	/www.reeve.com/SAM
	Nur 1 Ebene tief suchen:	
	Zu übertr. Dateitypen:	C Alle ፍ Nur diese: sam_data.png
OAA o A A - JU	Zu ignorierende Muster:	
	Fehler ignorieren:	🔽 Dateinamen wandeln: Nein: Beibehalten 💽
P IC I	Sounds abspielen:	Upload-Intervalit 1 Minute
in the Par	1 x alles hochladen:	Löschen von Dateien auf FTP-Server bestätigen:
Q/A	Watchdog aktiv:	Autostart dieser FTP-Verbindung aktivieren:
	84 	

SAM Magnetogram Thumbnail Image sent at 2 minute intervals (below)

🔏 FTP-Wato	hdog - [SAI	M_Magnetog	ram_Full_1mir	n]							×
Neu	Öffnen	Speichern	Protokoll	i öschen	Verz. öffne	n Hilfe	Info	Beenden	Ausblenden		
			Name des FTF	P-Servers:	reeve.com						Passives FTP:
			FTP-Benu FTP-	itzername: Passwort:	reevecom						
	ar		Lokales Ve	erzeichnis:	C:\Program	Files\SAM\Data\					
	20		FTP-Ve	erzeichnis:	/www.reeve	.com/SAM					
			Nur 1 Ebene tie	ef suchen:							
			Zu übertr. D	ateitypen:	C Alle 📀	Nur diese: sam	_small.png				
6.15	E.C		Zu ignorierend	de Muster:							
	2		Fehler i	gnorieren:		Dateinamen wande	In: Nein: Bei	behalten		.	
0	1	1	Sounds	abspielen:		Upload-Interv	all: 2 Minuter	n			
in.	24	260	1 x alles h	ochladen:		Löscher	n von Dateier	n auf FTP-Serv	er bestätigen:		
	S. Car		Watch	dog aktiv:		Au	utostart dieser	FTP-Verbindu	ng aktivieren:	v	
										100	

Appendix II – FTP-WatchDog Installation Sequence

1. When you run the installation program (ftp-watchdog-setup.exe), you may see a security warning (below). If so, click Run.

	Name:	ftp-watchdog-setup.exe	
	Publisher:	Unknown Publisher	
	Type:	Application	
	From:	C:\Documents and Settings\Whitham Reeve\My Do	
		Run Cancel]
🗸 Alwa	ays ask before	e opening this file	

2. Upon seeing the Welcome screen (below), click Continue (*Weiter*). In this and following windows, click Cancel (*Abbrechen*) if you wish to abort or cancel the installation or Back (*Zurűck*) if you wish to go back.



3. Read and accept the License (select upper radio button, *Ich akzeptiere die Bedingungen der Lizenzvereinbarung*, in screen below), click Continue (Weiter).



4. The next screen is Readme information, click Continue (*Weiter*).



5. Fill in the User Information (below), and click Continue (*Weiter*).

🙀 FTP-Watchdog - InstallShield Wiza	rd		×
Benutzerinformationen Geben Sie bitte Ihre Informationen ein	te		4
Benutzername:			
WR			
Organisation:			
None			
InstallShield			
	< Zurück	Weiter >	Abbrechen

6. Browse (*Andern*) to the target folder for the program files or accept the default (below), click Continue (*Weiter*).

🙀 FTP-Wat	chdog - InstallShield Wiza	rd		×
Zielordne Klicken S "Ändern	er Sie auf "Weiter", um diesen Ord ", um in einen anderen Ordner	lner zu installieren oo zu installieren.	der klicken Sie auf	
	Installiere FTP-Watchdog na C:\Program Files\Tools <u>M</u> ore\	ch: FTP-Watchdog\		Ändern
InstallShield -		< Zurück	Weiter >	Abbrechen

7. Finish installation (below), click Complete (*Fertigstellen*).

🚼 FTP-Watchdog - InstallShi	ield Wizard
	InstallShield Wizard abgeschlossen
	Der InstallShield Wizard hat FTP-Watchdog erfolgreich installiert. Klicken Sie auf "Fertigstellen", um den Assistenten zu verlassen.
	< Zarück Fertigstellen Abbrechen

8. When installation is finished, the default Settings window will open (below). At this time, your installation is complete and the Settings file is ready to be edited for your system.

4	tchdog - [Un	benannte FT	P-Einstellung]									
Neu	Öffnen	Speichern	Protokoll	löschen	Verz öffn	en Hilfe		1 Info	Beenden	Aushle	} nden	
HCG	onnen	operanerri	1100000	losenen	VCI2. OIIII	en mie		1110	beenden	Hubble	indiciti	
			Name des FT	P-Servers:	ihr.ftp-serve	er, xy						Passives FTP:
			FTP-Ben	utzername:	Benutzer-N	ame						
			FTP	P-Passwort:	*****							
			Lokales V	erzeichnis:	C:\Docume	ents and Setting	«\\i/hit	oam Beev	e۱			
1		-		arzeichnis:	/uorroichni	a lauf I dam Iaanu	5 111 III	ammeev				
		10	Nur 1 Ebene ti	ief suchen:		s/au/uem/serv	ei					
				or submorn.								
1	A 1	Section 1	1 Hai I Ebono a		Provent 1							
			Zu übertr. E) ateitypen:		Nurdiese:	htm .ht	ml .shtml .	pl .php .php3	l.php4.txt.i	nc .htt .jp	e .jpg .png .gif .com .ex
			Zu übertr. E Zu ignorieren	Dateitypen: ide Muster:		ONurdiese: ∏ ∖backups	htm . ht	ml . shtml .	pl .php .php3	l.php4.txt.i	nc .htt .jp	e .jpg .png .gif .com .ex
0			Zu übertr. E Zu ignorieren	Dateitypen: ide Muster:	Alle	Nur diese: [\backups	htm .ht	ml .shtml .	pl.php.php3	Lphp4.txt.i	nc .htt .jp	e.jpg.png.gif.com.ex
2.0			Zu übertr. E Zu ignorieren Fehler	Dateitypen: de Muster: ignorieren:	Alle Alle	0 Nur diese: \backups Dateinamen wa	htm .ht	ml.shtml.	pl .php .php3 behalten	3.php4.txt.i	nc .htt .jp	e .jpg .png .gif .com .ex
676-			Zu übertr. E Zu ignorieren Fehler Sounds	Dateitypen: de Muster: ignorieren: abspielen:	C Alle C	Nur diese: \backups Dateinamen wa Upload-In	htm .ht indeln: tervall:	ml .shtml . Nein: Bei sofort	pl.php.php3 behalten	l.php4.txt.i	nc .htt .jp	e .jpg .png .gif .com .ex
6-6-1		-	Zu übertr. E Zu ignorieren Fehler Sounds 1 x alles t	Dateitypen: de Muster: ignorieren: abspielen: hochladen:		Nur diese: [\backups Dateinamen wa Upload-In Lös	htm .ht indeln: tervall: chen vi	ml .shtml . Nein: Bei sofort on Dateier	pl.php.php3 behalten n auf FTP-Se	I.php4.txt.i	nchttjp	e .jpg .png .gif .com .ex

Document Information:

- Author: Whitham D. Reeve
- Revision: 0.0 (Original draft created, 2 Feb 2013)
 - 0.1 (Changed upload interval, 3 Feb 2013)
 - 0.2 (Minor edits, 5 Feb 2013)
 - 0.3 (Final draft, edits, added Appendix II, 26 Feb 2013)
 - 1.0 (Issued for distribution, 26 Feb 2013)